

CARRIER LOW TEMPERATURE 06D NOMENCLATURE

COMPRESSOR MODEL NO.	VOLT	HP	CFM	CFH	OIL CHG OZ.	MAX. WATTS	MAX. RLA	MTA	LRA
-------------------------	------	----	-----	-----	-------------------	---------------	-------------	-----	-----

2 CYLINDER

06DR1096-3100	575	2	8.7	522	56	3100	3.1	4.4	21.3
-3200	208/230	2	8.7	522	56	3100	8.8	12.1	53.3
-3600	460	2	8.7	522	56	3100	3.8	5.5	26.6

4 CYLINDER

06DR0136-3100	575	3	13.1	786	80	4300	5.6	7	28.4
-3200	208/230	3	13.1	786	80	4300	14	17.4	71
-3600	460	3	13.1	786	80	4300	7	8.7	35.5
06DR3166-3100	575	5	15.9	954	80	6250	8.6	10.8	40
-3200	208/230	5	15.9	954	80	6250	21.5	27	100
-3600	460	5	15.9	954	80	6250	10.8	13.5	50
06DR7186-3100	575	5	18.3	1100	112	6250	8.6	10.8	40
-3200	208/230	5	18.3	1100	112	6250	21.5	27	100
-3600	460	5	18.3	1100	112	6250	10.8	13.5	50
06DR8206-3100	575	6.5	20	1200	112	9800	12.6	17.6	64
-3200	208/230	6.5	20	1200	112	9800	31.5	44	160
-3600	460	6.5	20	1200	112	9800	15.7	22	80

6 CYLINDER

06DR7246-3100	575	6.5	23.9	1435	160	9800	12.6	17.6	64
-3200	208/230	6.5	23.9	1435	160	9800	31.5	44	160
-3600	460	6.5	23.9	1435	160	9800	15.7	22	80
06DR2286-3100	575	7.5	28	1680	160	12800	15.9	22.2	79
-3200	208/230	7.5	28	1680	160	12800	39.7	55.5	198
-3600	460	7.5	28	1680	160	12800	19.9	27.8	99
06DR3376-3100	575	10	37.1	2225	160	16500	17.9	25	91
-3200	208/230	10	37.1	2225	160	16500	44.3	62	228
-3600	460	10	37.1	2225	160	16500	22.1	31	114

MTA = MAXIMUM TRIP AMPS